

# Kima Warm Floor Cable Kit




Thin floor construction in wet and dry areas. Ordinary concrete constructions in wet and dry rooms.

## Product content:

- Heatingcable
- Thermostat
- Mounting
- Floor sensor tube

## Product specifications:

- Kima GG10.
- Kima Digital Zone 50.
- Kima Floor Mounting.



- 100 W/m<sup>2</sup> = C/C 10 cm
- 75 W/m<sup>2</sup> = C/C 13,5 cm
- 67 W/m<sup>2</sup> = C/C 15 cm
- 50 W/m<sup>2</sup> = C/C 20 cm
- 40 W/m<sup>2</sup> = C/C 25 cm

Part no.	EAN no.	Length (m)	Wattage (W)	m <sup>2</sup> *	Voltage (V)	Tolerance total (Ohm)
E 89 878 01	7331002902478	13	130	1,3	230	387 - 448
E 89 878 02	7331002902485	22	220	2,2	230	228 - 265
E 89 878 03	7331002902492	30	300	3,0	230	168 - 194
E 89 878 04	7331002902508	43	430	4,3	230	117 - 135
E 89 878 05	7331002902515	52	520	5,2	230	97 - 112
E 89 878 06	7331002902522	63	630	6,3	230	80 - 92
E 89 878 07	7331002902539	70	700	7,0	230	72 - 83
E 89 878 08	7331002902546	80	800	8,0	230	63 - 73
E 89 878 09	7331002902553	91	910	9,1	230	55 - 64
E 89 878 10	7331002902560	100	1000	10,0	230	50 - 58
E 89 878 11	7331002902577	117	1170	11,7	230	43 - 50
E 89 878 13	7331002902621	130	1300	13,0	230	39 - 45
E 89 878 14	7331002902584	142	1420	14,2	230	35 - 41
E 89 878 16	7331002902638	160	1600	16,0	230	31 - 36
E 89 877 18	7331002902591	182	1820	18,2	230	28 - 32

\* At 100 W/m<sup>2</sup> c/c 10 cm.

PRO00101008 07/0607

KIMA Heating Cable AB • Box 2024, SE-281 02 Hässleholm • Tel +46 451 38 30 60



www.kima.se